












| Type | n° | n° | n° |
|---------------------|----|----|----|
| AGRITECH 540 | 2 | 5 | 1 |



KIT Optional Art. 1220

|  |  |  |  |  |  |  |  |  |  |  | | | | | |
|---|---|---|---|---|---|---|--|---|---|---|--------|----|-----------|-----|-----|
| Type | lt. | Model | l/min | m ³ /h | r.p.m. | hp | r.p.m. | n° | stage n° | bar | p.s.i. | kg | L x B x H | | |
| AGRITECH 540 | 25 | K 18/C | 539 | 19 | 1400 | 20 | 250/325 | 2 | 1 | 11 | 160 | 88 | 680 | 670 | 850 |

Compressori portati attacco tre punti trattore

Sono caratterizzati da testate super professionali con cilindro e piatto valvole in ghisa, per un elevato rendimento ed una lunga durata. Il telaio compatto e robusto è dotato di gruppo filtro-riduttore-lubrificatore, manometri in bagno di glicerina e rubinetti rapidi multipli per il lavoro contemporaneo fino a 6 operatori.

La completezza della gamma da 540 a 1500 litri al minuto di aria aspirata rende i modelli della gamma Agritech adatti sia alla piccola che alla grande azienda. Tutti i modelli della serie Agritech sono predisposti per essere carrellati.

Compressors suitable to be attached to the three points of the tractor

Their super professional heads with cylinder and valve plate in cast iron assure a high performance and a long lasting work. The compact and solid frame is equipped with a filter-reducer-lubricator group, glycerine-bath pressure gauges and multiple rapid cocks which allows up to 6 operators working at the same time. All models of the line Agritech are suitable for both small and large farms thanks to their complete range from 540 to 1500 lt./min. of air displacement. All models of the line Agritech can be provided with wheels.